

## [MS-ASWBXML]:

# Exchange ActiveSync: WAP Binary XML (WBXML) Algorithm

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
12/3/2008	1.0.0	Major	Initial Release.
4/10/2009	2.0.0	Major	Updated technical content and applicable product releases.
7/15/2009	3.0.0	Major	Revised and edited for technical content.
11/4/2009	4.0.0	Major	Updated and revised the technical content.
2/10/2010	5.0.0	Major	Updated and revised the technical content.
5/5/2010	6.0.0	Major	Updated and revised the technical content.
8/4/2010	7.0	Major	Significantly changed the technical content.
11/3/2010	8.0	Major	Significantly changed the technical content.
3/18/2011	8.1	Minor	Clarified the meaning of the technical content.
8/5/2011	9.0	Major	Significantly changed the technical content.
10/7/2011	10.0	Major	Significantly changed the technical content.
1/20/2012	11.0	Major	Significantly changed the technical content.
4/27/2012	11.1	Minor	Clarified the meaning of the technical content.
7/16/2012	12.0	Major	Significantly changed the technical content.
10/8/2012	12.1	Minor	Clarified the meaning of the technical content.
2/11/2013	12.1	No Change	No changes to the meaning, language, or formatting of the technical content.
7/26/2013	13.0	Major	Significantly changed the technical content.
11/18/2013	13.0	No Change	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	13.0	No Change	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	14.0	Major	Significantly changed the technical content.
7/31/2014	14.0	No Change	No changes to the meaning, language, or formatting of the technical content.
10/30/2014	14.1	Minor	Clarified the meaning of the technical content.
5/26/2015	15.0	Major	Significantly changed the technical content.
6/30/2015	16.0	Major	Significantly changed the technical content.
9/14/2015	17.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>4</b>
1.1	Glossary .....	4
1.2	References .....	5
1.2.1	Normative References .....	5
1.2.2	Informative References .....	5
1.3	Overview .....	5
1.4	Relationship to Protocols and Other Algorithms .....	6
1.5	Applicability Statement .....	7
1.6	Standards Assignments.....	7
<b>2</b>	<b>Algorithm Details.....</b>	<b>8</b>
2.1	ActiveSync WBXML Algorithm Details.....	8
2.1.1	Abstract Data Model.....	8
2.1.2	Initialization.....	8
2.1.2.1	Code Pages .....	8
2.1.2.1.1	Code Page 0: AirSync .....	9
2.1.2.1.2	Code Page 1: Contacts .....	10
2.1.2.1.3	Code Page 2: Email .....	12
2.1.2.1.4	Code Page 3: AirNotify .....	14
2.1.2.1.5	Code Page 4: Calendar.....	15
2.1.2.1.6	Code Page 5: Move.....	16
2.1.2.1.7	Code Page 6: GetItemEstimate .....	17
2.1.2.1.8	Code Page 7: FolderHierarchy .....	17
2.1.2.1.9	Code Page 8: MeetingResponse.....	18
2.1.2.1.10	Code Page 9: Tasks .....	18
2.1.2.1.11	Code Page 10: ResolveRecipients .....	20
2.1.2.1.12	Code Page 11: ValidateCert .....	21
2.1.2.1.13	Code Page 12: Contacts2 .....	21
2.1.2.1.14	Code Page 13: Ping .....	22
2.1.2.1.15	Code Page 14: Provision.....	22
2.1.2.1.16	Code Page 15: Search.....	24
2.1.2.1.17	Code Page 16: GAL.....	25
2.1.2.1.18	Code Page 17: AirSyncBase .....	26
2.1.2.1.19	Code Page 18: Settings.....	27
2.1.2.1.20	Code Page 19: DocumentLibrary .....	29
2.1.2.1.21	Code Page 20: ItemOperations .....	29
2.1.2.1.22	Code Page 21: ComposeMail .....	30
2.1.2.1.23	Code Page 22: Email2 .....	31
2.1.2.1.24	Code Page 23: Notes .....	31
2.1.2.1.25	Code Page 24: RightsManagement.....	32
2.1.3	Processing Rules.....	33
<b>3</b>	<b>Algorithm Examples .....</b>	<b>34</b>
<b>4</b>	<b>Security .....</b>	<b>37</b>
4.1	Security Considerations for Implementers .....	37
4.2	Index of Security Parameters .....	37
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>38</b>
<b>6</b>	<b>Change Tracking.....</b>	<b>39</b>
<b>7</b>	<b>Index.....</b>	<b>41</b>

# 1 Introduction

The Exchange ActiveSync: WAP Binary XML (WBXML) Algorithm incorporates **Wireless Application Protocol (WAP) Binary XML (WBXML)** functionality into the ActiveSync protocols by mapping ActiveSync **XML schema** elements to numeric code page values. This enables ActiveSync clients to encode **XML** requests into WBXML for transmission to an ActiveSync server.

Section 2 of this specification is normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [\[RFC2119\]](#). Section 1.6 is also normative but does not contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are specific to this document:

**contact:** A person, company, or other entity that is stored in a directory and is associated with one or more unique identifiers and attributes (2), such as an Internet message address or login name.

**Hypertext Transfer Protocol (HTTP):** An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

**Secure Sockets Layer (SSL):** A security protocol that supports confidentiality and integrity of messages in client and server applications that communicate over open networks. SSL uses two keys to encrypt data—a public key known to everyone and a private or secret key known only to the recipient of the message. SSL supports server and, optionally, client authentication (2) using X.509 certificates (2). For more information, see [\[X509\]](#). The SSL protocol is precursor to Transport Layer Security (TLS). The TLS version 1.0 specification is based on SSL version 3.0 [\[SSL3\]](#).

**WBXML code page:** A map used to convert XML to Wireless Application Protocol (WAP) Binary XML (WBXML) that specifies the one-to-one relationships between the XML tags of a namespace and the tags' numeric representations called WBXML tokens. Each WBXML code page corresponds to an XML namespace.

**WBXML token:** A single-byte code that represents a specific XML tag.

**Wireless Application Protocol (WAP) Binary XML (WBXML):** A compact binary representation of **XML** that is designed to reduce the transmission size of XML documents over narrowband communication channels.

**XML:** The Extensible Markup Language, as described in [\[XML1.0\]](#).

**XML namespace:** A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [\[RFC3986\]](#). A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [\[XMLNS-2ED\]](#).

**XML schema:** A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by **XML** itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MS-ASCMD] Microsoft Corporation, "[Exchange ActiveSync: Command Reference Protocol](#)".

[MS-ASHTTP] Microsoft Corporation, "[Exchange ActiveSync: HTTP Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[WBXML1.2] Martin, B., and Jano, B., Eds., "WAP Binary XML Content Format", W3C Note, June 1999, <http://www.w3.org/1999/06/NOTE-wbxml-19990624>

### 1.2.2 Informative References

[MS-ASAIRS] Microsoft Corporation, "[Exchange ActiveSync: AirSyncBase Namespace Protocol](#)".

[MS-ASCAL] Microsoft Corporation, "[Exchange ActiveSync: Calendar Class Protocol](#)".

[MS-ASCNTC] Microsoft Corporation, "[Exchange ActiveSync: Contact Class Protocol](#)".

[MS-ASDOC] Microsoft Corporation, "[Exchange ActiveSync: Document Class Protocol](#)".

[MS-ASEMAIL] Microsoft Corporation, "[Exchange ActiveSync: Email Class Protocol](#)".

[MS-ASNOTE] Microsoft Corporation, "[Exchange ActiveSync: Notes Class Protocol](#)".

[MS-ASPROV] Microsoft Corporation, "[Exchange ActiveSync: Provisioning Protocol](#)".

[MS-ASRM] Microsoft Corporation, "[Exchange ActiveSync: Rights Management Protocol](#)".

[MS-ASTASK] Microsoft Corporation, "[Exchange ActiveSync: Tasks Class Protocol](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

## 1.3 Overview

This algorithm maps ActiveSync XML schema elements to numeric code page values for use by the ActiveSync protocols, enabling ActiveSync clients to encode WBXML requests for transmission to an ActiveSync server.

This algorithm provides **WBXML tokens** and **WBXML code pages** that allow clients and servers to compress the XML tags in request and response messages. WBXML code pages are hard-coded on the server and cannot be changed by the client. The WBXML code pages correspond to **XML namespaces**.

## 1.4 Relationship to Protocols and Other Algorithms

The XML namespaces that are used by this algorithm are described in the ActiveSync protocol specifications, as shown in the following table.

The WBXML code page numbers in the table are listed in decimal format.

WBXML code page	Specification
WBXML code page 0: AirSync	<a href="#">[MS-ASCMD]</a> section 2.2.2.20
WBXML code page 1: Contacts	<a href="#">[MS-ASCNTC]</a>
WBXML code page 2: Email	<a href="#">[MS-AEMAIL]</a>
WBXML code page 3: AirNotify	(no longer used)
WBXML code page 4: Calendar	<a href="#">[MS-ASCAL]</a>
WBXML code page 5: Move	[MS-ASCMD] section 2.2.2.11
WBXML code page 6: GetItemEstimate	[MS-ASCMD] section 2.2.2.8
WBXML code page 7: FolderHierarchy	[MS-ASCMD] sections 2.2.2.2, 2.2.2.3, 2.2.2.4, 2.2.2.5, and 2.2.2.7
WBXML code page 8: MeetingResponse	[MS-ASCMD] section 2.2.2.10
WBXML code page 9: Tasks	<a href="#">[MS-ASTASK]</a>
WBXML code page 10: ResolveRecipients	[MS-ASCMD] section 2.2.2.14
WBXML code page 11: ValidateCert	[MS-ASCMD] section 2.2.2.21
WBXML code page 12: Contacts2	[MS-ASCNTC]
WBXML code page 13: Ping	[MS-ASCMD] section 2.2.2.12
WBXML code page 14: Provision	<a href="#">[MS-ASPROV]</a>
WBXML code page 15: Search	[MS-ASCMD] section 2.2.2.15
WBXML code page 16: GAL	[MS-ASCMD] section 2.2.2.15
WBXML code page 17: AirSyncBase	<a href="#">[MS-ASAIRS]</a>
WBXML code page 18: Settings	[MS-ASCMD] section 2.2.2.17
WBXML code page 19: DocumentLibrary	<a href="#">[MS-ASDOC]</a>
WBXML code page 20: ItemOperations	[MS-ASCMD] sections 2.2.2.9
WBXML code page 21: ComposeMail	[MS-ASCMD] sections 2.2.2.16, 2.2.2.18, and 2.2.2.19
WBXML code page 22: Email2	[MS-AEMAIL]
WBXML code page 23: Notes	<a href="#">[MS-ASNOTE]</a>
WBXML code page 24: Rights Management	<a href="#">[MS-ASRM]</a>

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## 1.5 Applicability Statement

WBXML is used as a compact transmission format for mobile clients, which typically have little memory and bandwidth. WBXML encoding of XML tags is appropriate for all messages sent and received by using the ActiveSync protocols.

## 1.6 Standards Assignments

This algorithm uses the global WBXML tokens listed in the following table.

Token name	Token	Reference
SWITCH_PAGE	0	<a href="#">[WBXML1.2]</a>
END	1	[WBXML1.2]
ENTITY	2	[WBXML1.2]
STR_I	3	[WBXML1.2]
LITERAL	4	[WBXML1.2]
EXT_I_0	40	[WBXML1.2]
EXT_I_1	41	[WBXML1.2]
EXT_I_2	42	[WBXML1.2]
PI	43	[WBXML1.2]
LITERAL_C	44	[WBXML1.2]
EXT_T_0	80	[WBXML1.2]
EXT_T_1	81	[WBXML1.2]
EXT_T_2	82	[WBXML1.2]
STR_T	83	[WBXML1.2]
LITERAL_A	84	[WBXML1.2]
EXT_0	C0	[WBXML1.2]
EXT_1	C1	[WBXML1.2]
EXT_2	C2	[WBXML1.2]
OPAQUE	C3	[WBXML1.2]
LITERAL_AC	C4	[WBXML1.2]

## 2 Algorithm Details

### 2.1 ActiveSync WBXML Algorithm Details

ActiveSync messages are transported as HTTP **POST** messages, as specified in [\[MS-ASHTTP\]](#), where the body of the message contains WBXML formatted data. The WBXML data encodes the XML required by the command being communicated in the message. The ActiveSync commands are specified in [\[MS-ASCMD\]](#).

This section specifies the algorithm to encode XML request and response messages into WBXML format and to decode WBXML data into XML request and response messages. This algorithm is used by clients and servers.

#### 2.1.1 Abstract Data Model

None.

#### 2.1.2 Initialization

The XML tags in both request and response messages are encoded by using WBXML tokenization, as specified in [\[WBXML1.2\]](#). WBXML uses WBXML code pages to map XML tags to WBXML tokens. WBXML parsers MUST use the WBXML code pages specified in the following sections.

##### 2.1.2.1 Code Pages

This algorithm supports the following WBXML code pages.

Code page	XML namespace
0	AirSync
1	Contacts
2	Email
3	AirNotify
4	Calendar
5	Move
6	GetItemEstimate
7	FolderHierarchy
8	MeetingResponse
9	Tasks
10	ResolveRecipients
11	ValidateCert
12	Contacts2
13	Ping



Code page	XML namespace
14	Provision
15	Search
16	Gal
17	AirSyncBase
18	Settings
19	DocumentLibrary
20	ItemOperations
21	ComposeMail
22	Email2
23	Notes
24	RightsManagement

#### 2.1.2.1.1 Code Page 0: AirSync

The tags and tokens in WBXML code page 0 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Sync</b>	0x05	All
<b>Responses</b>	0x06	All
<b>Add</b>	0x07	All
<b>Change</b>	0x08	All
<b>Delete</b>	0x09	All
<b>Fetch</b>	0x0A	All
<b>SyncKey</b>	0x0B	All
<b>ClientId</b>	0x0C	All
<b>ServerId</b>	0x0D	All
<b>Status</b>	0x0E	All
<b>Collection</b>	0x0F	All
<b>Class</b>	0x10	All
<b>CollectionId</b>	0x12	All
<b>GetChanges</b>	0x13	All

Tag name	Token	Protocol versions
<b>MoreAvailable</b>	0x14	All
<b>WindowSize</b>	0x15	All
<b>Commands</b>	0x16	All
<b>Options</b>	0x17	All
<b>FilterType</b>	0x18	All
<b>Truncation</b>	0x19	2.5
<b>Conflict</b>	0x1B	All
<b>Collections</b>	0x1C	All
<b>ApplicationData</b>	0x1D	All
<b>DeletesAsMoves</b>	0x1E	All
<b>Supported</b>	0x20	All
<b>SoftDelete</b>	0x21	All
<b>MIMESupport</b>	0x22	All
<b>MIMETruncation</b>	0x23	All
<b>Wait</b>	0x24	12.1, 14.0, 14.1, 16.0
<b>Limit</b>	0x25	12.1, 14.0, 14.1, 16.0
<b>Partial</b>	0x26	12.1, 14.0, 14.1, 16.0
<b>ConversationMode</b>	0x27	14.0, 14.1, 16.0
<b>MaxItems</b>	0x28	14.0, 14.1, 16.0
<b>HeartbeatInterval</b>	0x29	14.0, 14.1, 16.0

### 2.1.2.1.2 Code Page 1: Contacts

The tags and tokens in WBXML code page 1 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Anniversary</b>	0x05	All
<b>AssistantName</b>	0x06	All
<b>AssistantPhoneNumber</b>	0x07	All
<b>Birthday</b>	0x08	All
<b>Body</b> — see note 1 following this table	0x09	2.5

Tag name	Token	Protocol versions
<b>BodySize</b>	0x0A	2.5
<b>BodyTruncated</b>	0x0B	2.5
<b>Business2PhoneNumber</b>	0x0C	All
<b>BusinessAddressCity</b>	0x0D	All
<b>BusinessAddressCountry</b>	0x0E	All
<b>BusinessAddressPostalCode</b>	0x0F	All
<b>BusinessAddressState</b>	0x10	All
<b>BusinessAddressStreet</b>	0x11	All
<b>BusinessFaxNumber</b>	0x12	All
<b>BusinessPhoneNumber</b>	0x13	All
<b>CarPhoneNumber</b>	0x14	All
<b>Categories</b>	0x15	All
<b>Category</b>	0x16	All
<b>Children</b>	0x17	All
<b>Child</b>	0x18	All
<b>CompanyName</b>	0x19	All
<b>Department</b>	0x1A	All
<b>Email1Address</b>	0x1B	All
<b>Email2Address</b>	0x1C	All
<b>Email3Address</b>	0x1D	All
<b>FileAs</b>	0x1E	All
<b>FirstName</b>	0x1F	All
<b>Home2PhoneNumber</b>	0x20	All
<b>HomeAddressCity</b>	0x21	All
<b>HomeAddressCountry</b>	0x22	All
<b>HomeAddressPostalCode</b>	0x23	All
<b>HomeAddressState</b>	0x24	All
<b>HomeAddressStreet</b>	0x25	All
<b>HomeFaxNumber</b>	0x26	All
<b>HomePhoneNumber</b>	0x27	All
<b>JobTitle</b>	0x28	All
<b>LastName</b>	0x29	All

Tag name	Token	Protocol versions
<b>MiddleName</b>	0x2A	All
<b>MobilePhoneNumber</b>	0x2B	All
<b>OfficeLocation</b>	0x2C	All
<b>OtherAddressCity</b>	0x2D	All
<b>OtherAddressCountry</b>	0x2E	All
<b>OtherAddressPostalCode</b>	0x2F	All
<b>OtherAddressState</b>	0x30	All
<b>OtherAddressStreet</b>	0x31	All
<b>PagerNumber</b>	0x32	All
<b>RadioPhoneNumber</b>	0x33	All
<b>Spouse</b>	0x34	All
<b>Suffix</b>	0x35	All
<b>Title</b>	0x36	All
<b>WebPage</b>	0x37	All
<b>YomiCompanyName</b>	0x38	All
<b>YomiFirstName</b>	0x39	All
<b>YomiLastName</b>	0x3A	All
<b>Picture</b>	0x3C	All
<b>Alias</b>	0x3D	14.0, 14.1, 16.0
<b>WeightedRank</b>	0x3E	14.0, 14.1, 16.0

**Note 1:** The **Body** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Body** tag in WBXML code page 1 with protocol versions 12.0, 12.1, 14.0, 14.1, and 16.0.

### 2.1.2.1.3 Code Page 2: Email

The tags and tokens in WBXML code page 2 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Attachment</b>	0x05	2.5
<b>Attachments</b> — see note 1 following this table	0x06	2.5
<b>AttName</b>	0x07	2.5
<b>AttSize</b>	0x08	2.5

Tag name	Token	Protocol versions
<b>Att0id</b>	0x09	2.5
<b>AttMethod</b>	0x0A	2.5
<b>Body</b> — see note 2 following this table	0x0C	2.5
<b>BodySize</b>	0x0D	2.5
<b>BodyTruncated</b>	0x0E	2.5
<b>DateReceived</b>	0x0F	All
<b>DisplayName</b>	0x10	2.5
<b>DisplayTo</b>	0x11	All
<b>Importance</b>	0x12	All
<b>MessageClass</b>	0x13	All
<b>Subject</b>	0x14	All
<b>Read</b>	0x15	All
<b>To</b>	0x16	All
<b>Cc</b>	0x17	All
<b>From</b>	0x18	All
<b>ReplyTo</b>	0x19	All
<b>AllDayEvent</b>	0x1A	All
<b>Categories</b>	0x1B	14.0, 14.1, 16.0
<b>Category</b>	0x1C	14.0, 14.1, 16.0
<b>DtStamp</b>	0x1D	All
<b>EndTime</b>	0x1E	All
<b>InstanceType</b>	0x1F	All
<b>BusyStatus</b>	0x20	All
<b>Location</b> — see note 3 following this table	0x21	2.5, 12.0, 12.1, 14.0, 14.1
<b>MeetingRequest</b>	0x22	All
<b>Organizer</b>	0x23	All
<b>RecurrenceId</b>	0x24	All
<b>Reminder</b>	0x25	All
<b>ResponseRequested</b>	0x26	All
<b>Recurrences</b>	0x27	All
<b>Recurrence</b>	0x28	All
<b>Type</b>	0x29	All

Tag name	Token	Protocol versions
<b>Until</b>	0x2A	All
<b>Occurrences</b>	0x2B	All
<b>Interval</b>	0x2C	All
<b>DayOfWeek</b>	0x2D	All
<b>DayOfMonth</b>	0x2E	All
<b>WeekOfMonth</b>	0x2F	All
<b>MonthOfYear</b>	0x30	All
<b>StartTime</b>	0x31	All
<b>Sensitivity</b>	0x32	All
<b>TimeZone</b>	0x33	All
<b>GlobalObjId</b> — see note 4 following this table	0x34	2.5, 12.0, 12.1, 14.0, 14.1
<b>ThreadTopic</b>	0x35	All
<b>MIMEData</b>	0x36	2.5
<b>MIMETruncated</b>	0x37	2.5
<b>MIMESize</b>	0x38	2.5
<b>InternetCPID</b>	0x39	All
<b>Flag</b>	0x3A	12.0, 12.1, 14.0, 14.1, 16.0
<b>Status</b>	0x3B	12.0, 12.1, 14.0, 14.1, 16.0
<b>ContentClass</b>	0x3C	12.0, 12.1, 14.0, 14.1, 16.0
<b>FlagType</b>	0x3D	12.0, 12.1, 14.0, 14.1, 16.0
<b>CompleteTime</b>	0x3E	12.0, 12.1, 14.0, 14.1, 16.0
<b>DisallowNewTimeProposal</b>	0x3F	14.0, 14.1, 16.0

**Note 1:** The **Attachments** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Attachments** tag in WBXML code page 2 with protocol versions 12.0, 12.1, 14.0, 14.1, and 16.0.

**Note 2:** The **Body** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Body** tag in WBXML code page 2 with protocol versions 12.0, 12.1, 14.0, 14.1, and 16.0.

**Note 3:** The **Location** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Location** tag in WBXML code page 2 with protocol version 16.0.

**Note 4:** The **UID** tag in WBXML code page 4 (Calendar) is used instead of the **GlobalObjId** tag in WBXML code page 2 with protocol version 16.0.

#### 2.1.2.1.4 Code Page 3: AirNotify

WBXML code page 3 is no longer in use.

### 2.1.2.1.5 Code Page 4: Calendar

The tags and tokens in WBXML code page 4 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Timezone</b>	0x05	All
<b>AllDayEvent</b>	0x06	All
<b>Attendees</b>	0x07	All
<b>Attendee</b>	0x08	All
<b>Email</b>	0x09	All
<b>Name</b>	0x0A	All
<b>Body</b> — see note 1 following this table	0x0B	2.5
<b>BodyTruncated</b>	0x0C	2.5
<b>BusyStatus</b>	0x0D	All
<b>Categories</b>	0x0E	All
<b>Category</b>	0x0F	All
<b>DtStamp</b>	0x11	All
<b>EndTime</b>	0x12	All
<b>Exception</b>	0x13	All
<b>Exceptions</b>	0x14	All
<b>Deleted</b>	0x15	All
<b>ExceptionStartTime</b>	0x16	2.5, 12.0, 12.1, 14.0, 14.1
<b>Location</b> — see note 2 following this table	0x17	2.5, 12.0, 12.1, 14.0, 14.1
<b>MeetingStatus</b>	0x18	All
<b>OrganizerEmail</b>	0x19	All
<b>OrganizerName</b>	0x1A	All
<b>Recurrence</b>	0x1B	All
<b>Type</b>	0x1C	All
<b>Until</b>	0x1D	All
<b>Occurrences</b>	0x1E	All
<b>Interval</b>	0x1F	All
<b>DayOfWeek</b>	0x20	All
<b>DayOfMonth</b>	0x21	All

Tag name	Token	Protocol versions
<b>WeekOfMonth</b>	0x22	All
<b>MonthOfYear</b>	0x23	All
<b>Reminder</b>	0x24	All
<b>Sensitivity</b>	0x25	All
<b>Subject</b>	0x26	All
<b>StartTime</b>	0x27	All
<b>UID</b>	0x28	All
<b>AttendeeStatus</b>	0x29	12.0, 12.1, 14.0, 14.1, 16.0
<b>AttendeeType</b>	0x2A	12.0, 12.1, 14.0, 14.1, 16.0
<b>DisallowNewTimeProposal</b>	0x33	14.0, 14.1, 16.0
<b>ResponseRequested</b>	0x34	14.0, 14.1, 16.0
<b>AppointmentReplyTime</b>	0x35	14.0, 14.1, 16.0
<b>ResponseType</b>	0x36	14.0, 14.1, 16.0
<b>CalendarType</b>	0x37	14.0, 14.1, 16.0
<b>IsLeapMonth</b>	0x38	14.0, 14.1, 16.0
<b>FirstDayOfWeek</b>	0x39	14.1, 16.0
<b>OnlineMeetingConfLink</b>	0x3A	14.1, 16.0
<b>OnlineMeetingExternalLink</b>	0x3B	14.1, 16.0
<b>ClientUid</b>	0x3C	16.0

**Note 1:** The **Body** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Body** tag in WBXML code page 4 with protocol versions 12.0, 12.1, 14.0, 14.1, and 16.0.

**Note 2:** The **Location** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Location** tag in WBXML code page 4 with protocol version 16.0.

#### 2.1.2.1.6 Code Page 5: Move

The tags and tokens in WBXML code page 5 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>MoveItems</b>	0x05	All
<b>Move</b>	0x06	All
<b>SrcMsgId</b>	0x07	All



Tag name	Token	Protocol versions
<b>SrcFldId</b>	0x08	All
<b>DstFldId</b>	0x09	All
<b>Response</b>	0x0A	All
<b>Status</b>	0x0B	All
<b>DstMsgId</b>	0x0C	All

#### 2.1.2.1.7 Code Page 6: GetItemEstimate

The tags and tokens in WBXML code page 6 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>GetItemEstimate</b>	0x05	All
<b>Collections</b>	0x07	All
<b>Collection</b>	0x08	All
<b>Class</b> — see note 1 following this table	0x09	2.5, 12.0, 12.1
<b>CollectionId</b>	0x0A	All
<b>Estimate</b>	0x0C	All
<b>Response</b>	0x0D	All
<b>Status</b>	0x0E	All

**Note 1:** The **Class** tag in WBXML code page 0 (AirSync) is used instead of the **Class** tag in WBXML code page 6 with protocol versions 14.0, 14.1, and 16.0.

#### 2.1.2.1.8 Code Page 7: FolderHierarchy

The tags and tokens in WBXML code page 7 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Folders</b>	0x05	2.5, 12.0, 12.1
<b>Folder</b>	0x06	2.5, 12.0, 12.1
<b>DisplayName</b>	0x07	All
<b>ServerId</b>	0x08	All

Tag name	Token	Protocol versions
<b>ParentId</b>	0x09	All
<b>Type</b>	0x0A	All
<b>Status</b>	0x0C	All
<b>Changes</b>	0x0E	All
<b>Add</b>	0x0F	All
<b>Delete</b>	0x10	All
<b>Update</b>	0x11	All
<b>SyncKey</b>	0x12	All
<b>FolderCreate</b>	0x13	All
<b>FolderDelete</b>	0x14	All
<b>FolderUpdate</b>	0x15	All
<b>FolderSync</b>	0x16	All
<b>Count</b>	0x17	All

#### 2.1.2.1.9 Code Page 8: MeetingResponse

The tags and tokens in WBXML code page 8 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>CalendarId</b>	0x05	All
<b>CollectionId</b>	0x06	All
<b>MeetingResponse</b>	0x07	All
<b>RequestId</b>	0x08	All
<b>Request</b>	0x09	All
<b>Result</b>	0x0A	All
<b>Status</b>	0x0B	All
<b>UserResponse</b>	0x0C	All
<b>InstanceId</b>	0x0E	14.1, 16.0
<b>SendResponse</b>	0x12	16.0

#### 2.1.2.1.10 Code Page 9: Tasks

The tags and tokens in WBXML code page 9 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Body</b> — see note 1 following this table	0x05	2.5
<b>BodySize</b>	0x06	2.5
<b>BodyTruncated</b>	0x07	2.5
<b>Categories</b>	0x08	All
<b>Category</b>	0x09	All
<b>Complete</b>	0x0A	All
<b>DateCompleted</b>	0x0B	All
<b>DueDate</b>	0x0C	All
<b>UtcDueDate</b>	0x0D	All
<b>Importance</b>	0x0E	All
<b>Recurrence</b>	0x0F	All
<b>Type</b>	0x10	All
<b>Start</b>	0x11	All
<b>Until</b>	0x12	All
<b>Occurrences</b>	0x13	All
<b>Interval</b>	0x14	All
<b>DayOfMonth</b>	0x15	All
<b>DayOfWeek</b>	0x16	All
<b>WeekOfMonth</b>	0x17	All
<b>MonthOfYear</b>	0x18	All
<b>Regenerate</b>	0x19	All
<b>DeadOccur</b>	0x1A	All
<b>ReminderSet</b>	0x1B	All
<b>ReminderTime</b>	0x1C	All
<b>Sensitivity</b>	0x1D	All
<b>StartDate</b>	0x1E	All
<b>UtcStartDate</b>	0x1F	All
<b>Subject</b>	0x20	All
<b>OrdinalDate</b>	0x22	12.0, 12.1, 14.0, 14.1, 16.0

Tag name	Token	Protocol versions
<b>SubOrdinalDate</b>	0x23	12.0, 12.1, 14.0, 14.1, 16.0
<b>CalendarType</b>	0x24	14.0, 14.1, 16.0
<b>IsLeapMonth</b>	0x25	14.0, 14.1, 16.0
<b>FirstDayOfWeek</b>	0x26	14.1, 16.0

**Note 1:** The **Body** tag in WBXML code page 17 (AirSyncBase) is used instead of the **Body** tag in WBXML code page 9 with protocol versions 12.0, 12.1, 14.0, 14.1, and 16.0.

### 2.1.2.1.11 Code Page 10: ResolveRecipients

The tags and tokens in WBXML code page 10 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>ResolveRecipients</b>	0x05	All
<b>Response</b>	0x06	All
<b>Status</b>	0x07	All
<b>Type</b>	0x08	All
<b>Recipient</b>	0x09	All
<b>DisplayName</b>	0x0A	All
<b>EmailAddress</b>	0x0B	All
<b>Certificates</b>	0x0C	All
<b>Certificate</b>	0x0D	All
<b>MiniCertificate</b>	0x0E	All
<b>Options</b>	0x0F	All
<b>To</b>	0x10	All
<b>CertificateRetrieval</b>	0x11	All
<b>RecipientCount</b>	0x12	All
<b>MaxCertificates</b>	0x13	All
<b>MaxAmbiguousRecipients</b>	0x14	All
<b>CertificateCount</b>	0x15	All
<b>Availability</b>	0x16	14.0, 14.1, 16.0
<b>StartTime</b>	0x17	14.0, 14.1, 16.0
<b>EndTime</b>	0x18	14.0, 14.1, 16.0

Tag name	Token	Protocol versions
<b>MergedFreeBusy</b>	0x19	14.0, 14.1, 16.0
<b>Picture</b>	0x1A	14.1, 16.0
<b>MaxSize</b>	0x1B	14.1, 16.0
<b>Data</b>	0x1C	14.1, 16.0
<b>MaxPictures</b>	0x1D	14.1, 16.0

#### 2.1.2.1.12 Code Page 11: ValidateCert

The tags and tokens in WBXML code page 11 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>ValidateCert</b>	0x05	All
<b>Certificates</b>	0x06	All
<b>Certificate</b>	0x07	All
<b>CertificateChain</b>	0x08	All
<b>CheckCRL</b>	0x09	All
<b>Status</b>	0x0A	All

#### 2.1.2.1.13 Code Page 12: Contacts2

The tags and tokens in WBXML code page 12 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>CustomerId</b>	0x05	All
<b>GovernmentId</b>	0x06	All
<b>IMAddress</b>	0x07	All
<b>IMAddress2</b>	0x08	All
<b>IMAddress3</b>	0x09	All
<b>ManagerName</b>	0x0A	All
<b>CompanyMainPhone</b>	0x0B	All
<b>AccountName</b>	0x0C	All

Tag name	Token	Protocol versions
NickName	0x0D	All
MMS	0x0E	All

#### 2.1.2.1.14 Code Page 13: Ping

The tags and tokens in WBXML code page 13 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
Ping	0x05	All
Status	0x07	All
HeartbeatInterval	0x08	All
Folders	0x09	All
Folder	0x0A	All
Id	0x0B	All
Class	0x0C	All
MaxFolders	0x0D	All

#### 2.1.2.1.15 Code Page 14: Provision

The tags and tokens in WBXML code page 14 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
Provision	0x05	All
Policies	0x06	All
Policy	0x07	All
PolicyType	0x08	All
PolicyKey	0x09	All
Data	0x0A	All
Status	0x0B	All
RemoteWipe	0x0C	All
EASProvisionDoc	0x0D	12.0, 12.1, 14.0, 14.1, 16.0

Tag name	Token	Protocol versions
<b>DevicePasswordEnabled</b>	0x0E	12.0, 12.1, 14.0, 14.1, 16.0
<b>AlphanumericDevicePasswordRequired</b>	0x0F	12.0, 12.1, 14.0, 14.1, 16.0
<b>RequireStorageCardEncryption</b>	0x10	12.1, 14.0, 14.1, 16.0
<b>PasswordRecoveryEnabled</b>	0x11	12.0, 12.1, 14.0, 14.1, 16.0
<b>AttachmentsEnabled</b>	0x13	12.0, 12.1, 14.0, 14.1, 16.0
<b>MinDevicePasswordLength</b>	0x14	12.0, 12.1, 14.0, 14.1, 16.0
<b>MaxInactivityTimeDeviceLock</b>	0x15	12.0, 12.1, 14.0, 14.1, 16.0
<b>MaxDevicePasswordFailedAttempts</b>	0x16	12.0, 12.1, 14.0, 14.1, 16.0
<b>MaxAttachmentSize</b>	0x17	12.0, 12.1, 14.0, 14.1, 16.0
<b>AllowSimpleDevicePassword</b>	0x18	12.0, 12.1, 14.0, 14.1, 16.0
<b>DevicePasswordExpiration</b>	0x19	12.0, 12.1, 14.0, 14.1, 16.0
<b>DevicePasswordHistory</b>	0x1A	12.0, 12.1, 14.0, 14.1, 16.0
<b>AllowStorageCard</b>	0x1B	12.1, 14.0, 14.1, 16.0
<b>AllowCamera</b>	0x1C	12.1, 14.0, 14.1, 16.0
<b>RequireDeviceEncryption</b>	0x1D	12.1, 14.0, 14.1, 16.0
<b>AllowUnsignedApplications</b>	0x1E	12.1, 14.0, 14.1, 16.0
<b>AllowUnsignedInstallationPackages</b>	0x1F	12.1, 14.0, 14.1, 16.0
<b>MinDevicePasswordComplexCharacters</b>	0x20	12.1, 14.0, 14.1, 16.0
<b>AllowWiFi</b>	0x21	12.1, 14.0, 14.1, 16.0
<b>AllowTextMessaging</b>	0x22	12.1, 14.0, 14.1, 16.0
<b>AllowPOPIMAPEmail</b>	0x23	12.1, 14.0, 14.1, 16.0
<b>AllowBluetooth</b>	0x24	12.1, 14.0, 14.1, 16.0
<b>AllowIrDA</b>	0x25	12.1, 14.0, 14.1, 16.0
<b>RequireManualSyncWhenRoaming</b>	0x26	12.1, 14.0, 14.1, 16.0
<b>AllowDesktopSync</b>	0x27	12.1, 14.0, 14.1, 16.0
<b>MaxCalendarAgeFilter</b>	0x28	12.1, 14.0, 14.1, 16.0
<b>AllowHTMLEmail</b>	0x29	12.1, 14.0, 14.1, 16.0
<b>MaxEmailAgeFilter</b>	0x2A	12.1, 14.0, 14.1, 16.0
<b>MaxEmailBodyTruncationSize</b>	0x2B	12.1, 14.0, 14.1, 16.0
<b>MaxEmailHTMLBodyTruncationSize</b>	0x2C	12.1, 14.0, 14.1, 16.0
<b>RequireSignedSMIMEMessages</b>	0x2D	12.1, 14.0, 14.1, 16.0
<b>RequireEncryptedSMIMEMessages</b>	0x2E	12.1, 14.0, 14.1, 16.0

Tag name	Token	Protocol versions
<b>RequireSignedSMIMEAlgorithm</b>	0x2F	12.1, 14.0, 14.1, 16.0
<b>RequireEncryptionSMIMEAlgorithm</b>	0x30	12.1, 14.0, 14.1, 16.0
<b>AllowSMIMEEncryptionAlgorithmNegotiation</b>	0x31	12.1, 14.0, 14.1, 16.0
<b>AllowSMIMESoftCerts</b>	0x32	12.1, 14.0, 14.1, 16.0
<b>AllowBrowser</b>	0x33	12.1, 14.0, 14.1, 16.0
<b>AllowConsumerEmail</b>	0x34	12.1, 14.0, 14.1, 16.0
<b>AllowRemoteDesktop</b>	0x35	12.1, 14.0, 14.1, 16.0
<b>AllowInternetSharing</b>	0x36	12.1, 14.0, 14.1, 16.0
<b>UnapprovedInROMApplicationList</b>	0x37	12.1, 14.0, 14.1, 16.0
<b>ApplicationName</b>	0x38	12.1, 14.0, 14.1, 16.0
<b>ApprovedApplicationList</b>	0x39	12.1, 14.0, 14.1, 16.0
<b>Hash</b>	0x3A	12.1, 14.0, 14.1, 16.0

#### 2.1.2.1.16 Code Page 15: Search

The tags and tokens in WBXML code page 15 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Search</b>	0x05	All
<b>Store</b>	0x07	All
<b>Name</b>	0x08	All
<b>Query</b>	0x09	All
<b>Options</b>	0x0A	All
<b>Range</b>	0x0B	All
<b>Status</b>	0x0C	All
<b>Response</b>	0x0D	All
<b>Result</b>	0x0E	All
<b>Properties</b>	0x0F	All
<b>Total</b>	0x10	All
<b>EqualTo</b>	0x11	12.0, 12.1, 14.0, 14.1, 16.0
<b>Value</b>	0x12	12.0, 12.1, 14.0, 14.1, 16.0



Tag name	Token	Protocol versions
<b>And</b>	0x13	12.0, 12.1, 14.0, 14.1, 16.0
<b>Or</b>	0x14	12.0, 12.1, 14.0, 14.1, 16.0
<b>FreeText</b>	0x15	12.0, 12.1, 14.0, 14.1, 16.0
<b>DeepTraversal</b>	0x17	12.0, 12.1, 14.0, 14.1, 16.0
<b>LongId</b>	0x18	12.0, 12.1, 14.0, 14.1, 16.0
<b>RebuildResults</b>	0x19	12.0, 12.1, 14.0, 14.1, 16.0
<b>LessThan</b>	0x1A	12.0, 12.1, 14.0, 14.1, 16.0
<b>GreaterThan</b>	0x1B	12.0, 12.1, 14.0, 14.1, 16.0
<b>UserName</b>	0x1E	12.1, 14.0, 14.1, 16.0
<b>Password</b>	0x1F	12.1, 14.0, 14.1, 16.0
<b>ConversationId</b>	0x20	14.0, 14.1, 16.0
<b>Picture</b>	0x21	14.1, 16.0
<b>MaxSize</b>	0x22	14.1, 16.0
<b>MaxPictures</b>	0x23	14.1, 16.0

#### 2.1.2.1.17 Code Page 16: GAL

The tags and tokens in WBXML code page 16 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>DisplayName</b>	0x05	All
<b>Phone</b>	0x06	All
<b>Office</b>	0x07	All
<b>Title</b>	0x08	All
<b>Company</b>	0x09	All
<b>Alias</b>	0x0A	All
<b>FirstName</b>	0x0B	All
<b>LastName</b>	0x0C	All
<b>HomePhone</b>	0x0D	All
<b>MobilePhone</b>	0x0E	All
<b>EmailAddress</b>	0x0F	All

Tag name	Token	Protocol versions
<b>Picture</b>	0x10	14.1, 16.0
<b>Status</b>	0x11	14.1, 16.0
<b>Data</b>	0x12	14.1, 16.0

#### 2.1.2.1.18 Code Page 17: AirSyncBase

The tags and tokens in WBXML code page 17 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>BodyPreference</b>	0x05	12.0, 12.1, 14.0, 14.1, 16.0
<b>Type</b>	0x06	12.0, 12.1, 14.0, 14.1, 16.0
<b>TruncationSize</b>	0x07	12.0, 12.1, 14.0, 14.1, 16.0
<b>AllOrNone</b>	0x08	12.0, 12.1, 14.0, 14.1, 16.0
<b>Body</b>	0x0A	12.0, 12.1, 14.0, 14.1, 16.0
<b>Data</b>	0x0B	12.0, 12.1, 14.0, 14.1, 16.0
<b>EstimatedDataSize</b>	0x0C	12.0, 12.1, 14.0, 14.1, 16.0
<b>Truncated</b>	0x0D	12.0, 12.1, 14.0, 14.1, 16.0
<b>Attachments</b>	0x0E	12.0, 12.1, 14.0, 14.1, 16.0
<b>Attachment</b>	0x0F	12.0, 12.1, 14.0, 14.1, 16.0
<b>DisplayName</b>	0x10	12.0, 12.1, 14.0, 14.1, 16.0
<b>FileReference</b>	0x11	12.0, 12.1, 14.0, 14.1, 16.0
<b>Method</b>	0x12	12.0, 12.1, 14.0, 14.1, 16.0
<b>ContentId</b>	0x13	12.0, 12.1, 14.0, 14.1, 16.0
<b>ContentLocation</b>	0x14	12.0, 12.1, 14.0, 14.1, 16.0
<b>IsInline</b>	0x15	12.0, 12.1, 14.0, 14.1, 16.0
<b>NativeBodyType</b>	0x16	12.0, 12.1, 14.0, 14.1, 16.0
<b>ContentType</b>	0x17	12.0, 12.1, 14.0, 14.1, 16.0
<b>Preview</b>	0x18	14.0, 14.1, 16.0
<b>BodyPartPreference</b>	0x19	14.1, 16.0
<b>BodyPart</b>	0x1A	14.1, 16.0
<b>Status</b>	0x1B	14.1, 16.0

Tag name	Token	Protocol versions
<b>Add</b>	0x1C	16.0
<b>Delete</b>	0x1D	16.0
<b>ClientId</b>	0x1E	16.0
<b>Content</b>	0x1F	16.0
<b>Location</b>	0x20	16.0
<b>Annotation</b>	0x21	16.0
<b>Street</b>	0x22	16.0
<b>City</b>	0x23	16.0
<b>State</b>	0x24	16.0
<b>Country</b>	0x25	16.0
<b>PostalCode</b>	0x26	16.0
<b>Latitude</b>	0x27	16.0
<b>Longitude</b>	0x28	16.0
<b>Accuracy</b>	0x29	16.0
<b>Altitude</b>	0x2A	16.0
<b>AltitudeAccuracy</b>	0x2B	16.0
<b>LocationUri</b>	0x2C	16.0
<b>InstanceId</b>	0x2D	16.0

#### 2.1.2.1.19 Code Page 18: Settings

The tags and tokens in WBXML code page 18 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Settings</b>	0x05	12.0, 12.1, 14.0, 14.1, 16.0
<b>Status</b>	0x06	12.0, 12.1, 14.0, 14.1, 16.0
<b>Get</b>	0x07	12.0, 12.1, 14.0, 14.1, 16.0
<b>Set</b>	0x08	12.0, 12.1, 14.0, 14.1, 16.0
<b>Oof</b>	0x09	12.0, 12.1, 14.0, 14.1, 16.0
<b>OofState</b>	0x0A	12.0, 12.1, 14.0, 14.1, 16.0
<b>StartTime</b>	0x0B	12.0, 12.1, 14.0, 14.1, 16.0

Tag name	Token	Protocol versions
<b>EndTime</b>	0x0C	12.0, 12.1, 14.0, 14.1, 16.0
<b>OofMessage</b>	0x0D	12.0, 12.1, 14.0, 14.1, 16.0
<b>AppliesToInternal</b>	0x0E	12.0, 12.1, 14.0, 14.1, 16.0
<b>AppliesToExternalKnown</b>	0x0F	12.0, 12.1, 14.0, 14.1, 16.0
<b>AppliesToExternalUnknown</b>	0x10	12.0, 12.1, 14.0, 14.1, 16.0
<b>Enabled</b>	0x11	12.0, 12.1, 14.0, 14.1, 16.0
<b>ReplyMessage</b>	0x12	12.0, 12.1, 14.0, 14.1, 16.0
<b>BodyType</b>	0x13	12.0, 12.1, 14.0, 14.1, 16.0
<b>DevicePassword</b>	0x14	12.0, 12.1, 14.0, 14.1, 16.0
<b>Password</b>	0x15	12.0, 12.1, 14.0, 14.1, 16.0
<b>DeviceInformation</b>	0x16	12.0, 12.1, 14.0, 14.1, 16.0
<b>Model</b>	0x17	12.0, 12.1, 14.0, 14.1, 16.0
<b>IMEI</b>	0x18	12.0, 12.1, 14.0, 14.1, 16.0
<b>FriendlyName</b>	0x19	12.0, 12.1, 14.0, 14.1, 16.0
<b>OS</b>	0x1A	12.0, 12.1, 14.0, 14.1, 16.0
<b>OSLanguage</b>	0x1B	12.0, 12.1, 14.0, 14.1, 16.0
<b>PhoneNumber</b>	0x1C	12.0, 12.1, 14.0, 14.1, 16.0
<b>UserInformation</b>	0x1D	12.0, 12.1, 14.0, 14.1, 16.0
<b>EmailAddresses</b>	0x1E	12.0, 12.1, 14.0, 14.1, 16.0
<b>SMTPAddress</b>	0x1F	12.0, 12.1, 14.0, 14.1, 16.0
<b>UserAgent</b>	0x20	12.1, 14.0, 14.1, 16.0
<b>EnableOutboundSMS</b>	0x21	14.0, 14.1, 16.0
<b>MobileOperator</b>	0x22	14.0, 14.1, 16.0
<b>PrimarySmtpAddress</b>	0x23	14.1, 16.0
<b>Accounts</b>	0x24	14.1, 16.0
<b>Account</b>	0x25	14.1, 16.0
<b>AccountId</b>	0x26	14.1, 16.0
<b>AccountName</b>	0x27	14.1, 16.0
<b>UserDisplayName</b>	0x28	14.1, 16.0
<b>SendDisabled</b>	0x29	14.1, 16.0
<b>RightsManagementInformation</b>	0x2B	14.1, 16.0

### 2.1.2.1.20 Code Page 19: DocumentLibrary

The tags and tokens in WBXML code page 19 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>LinkId</b>	0x05	12.0, 12.1, 14.0, 14.1, 16.0
<b>DisplayName</b>	0x06	12.0, 12.1, 14.0, 14.1, 16.0
<b>IsFolder</b>	0x07	12.0, 12.1, 14.0, 14.1, 16.0
<b>CreationDate</b>	0x08	12.0, 12.1, 14.0, 14.1, 16.0
<b>LastModifiedDate</b>	0x09	12.0, 12.1, 14.0, 14.1, 16.0
<b>IsHidden</b>	0x0A	12.0, 12.1, 14.0, 14.1, 16.0
<b>ContentLength</b>	0x0B	12.0, 12.1, 14.0, 14.1, 16.0
<b>ContentType</b>	0x0C	12.0, 12.1, 14.0, 14.1, 16.0

### 2.1.2.1.21 Code Page 20: ItemOperations

The tags and tokens in WBXML code page 20 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>ItemOperations</b>	0x05	12.0, 12.1, 14.0, 14.1, 16.0
<b>Fetch</b>	0x06	12.0, 12.1, 14.0, 14.1, 16.0
<b>Store</b>	0x07	12.0, 12.1, 14.0, 14.1, 16.0
<b>Options</b>	0x08	12.0, 12.1, 14.0, 14.1, 16.0
<b>Range</b>	0x09	12.0, 12.1, 14.0, 14.1, 16.0
<b>Total</b>	0x0A	12.0, 12.1, 14.0, 14.1, 16.0
<b>Properties</b>	0x0B	12.0, 12.1, 14.0, 14.1, 16.0
<b>Data</b>	0x0C	12.0, 12.1, 14.0, 14.1, 16.0
<b>Status</b>	0x0D	12.0, 12.1, 14.0, 14.1, 16.0
<b>Response</b>	0x0E	12.0, 12.1, 14.0, 14.1, 16.0
<b>Version</b>	0x0F	12.0, 12.1, 14.0, 14.1, 16.0
<b>Schema</b>	0x10	12.0, 12.1, 14.0, 14.1, 16.0
<b>Part</b>	0x11	12.0, 12.1, 14.0, 14.1, 16.0

Tag name	Token	Protocol versions
<b>EmptyFolderContents</b>	0x12	12.0, 12.1, 14.0, 14.1, 16.0
<b>DeleteSubFolders</b>	0x13	12.0, 12.1, 14.0, 14.1, 16.0
<b>UserName</b>	0x14	12.1, 14.0, 14.1, 16.0
<b>Password</b>	0x15	12.1, 14.0, 14.1, 16.0
<b>Move</b>	0x16	14.0, 14.1, 16.0
<b>DstFldId</b>	0x17	14.0, 14.1, 16.0
<b>ConversationId</b>	0x18	14.0, 14.1, 16.0
<b>MoveAlways</b>	0x19	14.0, 14.1, 16.0

### 2.1.2.1.22 Code Page 21: ComposeMail

The tags and tokens in WBXML code page 21 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>SendMail</b>	0x05	14.0, 14.1, 16.0
<b>SmartForward</b>	0x06	14.0, 14.1, 16.0
<b>SmartReply</b>	0x07	14.0, 14.1, 16.0
<b>SaveInSentItems</b>	0x08	14.0, 14.1, 16.0
<b>ReplaceMime</b>	0x09	14.0, 14.1, 16.0
<b>Source</b>	0x0B	14.0, 14.1, 16.0
<b>FolderId</b>	0x0C	14.0, 14.1, 16.0
<b>ItemId</b>	0x0D	14.0, 14.1, 16.0
<b>LongId</b>	0x0E	14.0, 14.1, 16.0
<b>InstanceId</b>	0x0F	14.0, 14.1, 16.0
<b>Mime</b>	0x10	14.0, 14.1, 16.0
<b>ClientId</b>	0x11	14.0, 14.1, 16.0
<b>Status</b>	0x12	14.0, 14.1, 16.0
<b>AccountId</b>	0x13	14.1, 16.0
<b>Forwardees</b>	0x15	16.0
<b>Forwarder</b>	0x16	16.0
<b>ForwarderName</b>	0x17	16.0

Tag name	Token	Protocol versions
ForwarderEmail	0x18	16.0

### 2.1.2.1.23 Code Page 22: Email2

The tags and tokens in WBXML code page 22 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
UmCallerID	0x05	14.0, 14.1, 16.0
UmUserNotes	0x06	14.0, 14.1, 16.0
UmAttDuration	0x07	14.0, 14.1, 16.0
UmAttOrder	0x08	14.0, 14.1, 16.0
ConversationId	0x09	14.0, 14.1, 16.0
ConversationIndex	0x0A	14.0, 14.1, 16.0
LastVerbExecuted	0x0B	14.0, 14.1, 16.0
LastVerbExecutionTime	0x0C	14.0, 14.1, 16.0
ReceivedAsBcc	0x0D	14.0, 14.1, 16.0
Sender	0x0E	14.0, 14.1, 16.0
CalendarType	0x0F	14.0, 14.1, 16.0
IsLeapMonth	0x10	14.0, 14.1, 16.0
AccountId	0x11	14.1, 16.0
FirstDayOfWeek	0x12	14.1, 16.0
MeetingMessageType	0x13	14.1, 16.0
IsDraft	0x15	16.0
Bcc	0x16	16.0
Send	0x17	16.0

### 2.1.2.1.24 Code Page 23: Notes

The tags and tokens in WBXML code page 23 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>Subject</b>	0x05	14.0, 14.1, 16.0
<b>MessageClass</b>	0x06	14.0, 14.1, 16.0
<b>LastModifiedDate</b>	0x07	14.0, 14.1, 16.0
<b>Categories</b>	0x08	14.0, 14.1, 16.0
<b>Category</b>	0x09	14.0, 14.1, 16.0

### 2.1.2.1.25 Code Page 24: RightsManagement

The tags and tokens in WBXML code page 24 are listed in the following table. The ActiveSync protocol versions that support each tag/token are specified in the "Protocol versions" column of the table. For details about the ActiveSync protocol versions that can be used by a client or a server, see [\[MS-ASHTTP\]](#).

Tag name	Token	Protocol versions
<b>RightsManagementSupport</b>	0x05	14.1, 16.0
<b>RightsManagementTemplates</b>	0x06	14.1, 16.0
<b>RightsManagementTemplate</b>	0x07	14.1, 16.0
<b>RightsManagementLicense</b>	0x08	14.1, 16.0
<b>EditAllowed</b>	0x09	14.1, 16.0
<b>ReplyAllowed</b>	0x0A	14.1, 16.0
<b>ReplyAllAllowed</b>	0x0B	14.1, 16.0
<b>ForwardAllowed</b>	0x0C	14.1, 16.0
<b>ModifyRecipientsAllowed</b>	0x0D	14.1, 16.0
<b>ExtractAllowed</b>	0x0E	14.1, 16.0
<b>PrintAllowed</b>	0x0F	14.1, 16.0
<b>ExportAllowed</b>	0x10	14.1, 16.0
<b>ProgrammaticAccessAllowed</b>	0x11	14.1, 16.0
<b>Owner</b>	0x12	14.1, 16.0
<b>ContentExpiryDate</b>	0x13	14.1, 16.0
<b>TemplateID</b>	0x14	14.1, 16.0
<b>TemplateName</b>	0x15	14.1, 16.0
<b>TemplateDescription</b>	0x16	14.1, 16.0
<b>ContentOwner</b>	0x17	14.1, 16.0
<b>RemoveRightsManagementProtection</b>	0x18	14.1, 16.0



### 2.1.3 Processing Rules

The processing rules for this algorithm are specified in [\[WBXML1.2\]](#).

This algorithm uses the following features that are specified in [WBXML1.2]:

- WBXML tokens to encode XML tags
- WBXML code pages to support multiple XML namespaces
- Inline strings
- Opaque data

This algorithm does not use the following features that are specified in [WBXML1.2]:

- String tables
- Entities
- Processing instructions
- Attribute encoding

### 3 Algorithm Examples

The following example shows the WBXML encoding of a server response that contains a new **contact** and provides a byte-by-byte description of the encoding.

The following XML represents a server response to a request to create a new contact.

```
<?xml version="1.0" encoding="utf-8"?>
<Sync xmlns="AirSync" xmlns:airsyncbase="AirSyncBase" xmlns:contacts="Contacts">
  <Collections>
    <Collection>
      <Class>Contacts</Class>
      <SyncKey>2</SyncKey>
      <CollectionId>2</CollectionId>
      <Status>1</Status>
      <Commands>
        <Add>
          <ServerId>2:1</ServerId>
          <ApplicationData>
            <airsyncbase:Body>
              <airsyncbase:Type>1</airsyncbase:Type>
              <airsyncbase:EstimatedDataSize>0</airsyncbase:EstimatedDataSize>
              <airsyncbase:Truncated>1</airsyncbase:Truncated>
            </airsyncbase:Body>
            <contacts:FileAs>Funk, Don</contacts:FileAs>
            <contacts:FirstName>Don</contacts:FirstName>
            <contacts:LastName>Funk</contacts:LastName>
            <airsyncbase:NativeBodyType>1</airsyncbase:NativeBodyType>
          </ApplicationData>
        </Add>
      </Commands>
    </Collection>
  </Collections>
</Sync>
```

The Exchange ActiveSync: WAP Binary XML (WBXML) Algorithm encodes this XML as the following WBXML encoding.

```
03 01 6A 00 45 5C 4F 50 03 43 6F 6E 74 61 63 74 73 00 01 4B 03 32 00 01 52 03 32 00 01 4E 03
31 00 01 56 47 4D 03 32 3A 31 00 01 5D 00 11 4A 46 03 31 00 01 4C 03 30 00 01 4D 03 31 00 01
01 00 01 5E 03 46 75 6E 6B 2C 20 44 6F 6E 00 01 5F 03 44 6F 6E 00 01 69 03 46 75 6E 6B 00 01
00 11 56 03 31 00 01 01 01 01 01 01 01
```

The following table explains each byte in the WBXML encoding.

Bytes	Description
03	Version number – WBXML version 1.3
01	Unknown public identifier
6A	Charset = UTF-8
00	String table length
45	<airsync:Sync>, with content (0x05 + 0x40)
5C	<airsync:Collections>, with content
4F	<airsync:Collection>, with content

Bytes	Description
50	<airsync:Class>, with content
03	Inline string follows
43 6F 6E 74 61 63 74 73 00	"contacts" (the 00 is the end of the string)
01	</airsync:Class>
4B	<airsync:SyncKey>, with content
03	Inline string follows
32 00	"2"
01	</airsync:SyncKey>
52	<airsync:CollectionID>, with content
03	Inline string follows
32 00	"2"
01	</airsync:CollectionID>
4E	<airsync:Status>, with content
03	Inline string follows
31 00	"1"
01	</airsync:Status>
56	<airsync:Commands>, with content
47	<airsync:Add>, with content
4D	<airsync:ServerId>, with content
03	Inline string follows
32 3A 31 00	"2:1"
01	</airsync:ServerId>
5D	<airsync:ApplicationData>, with content
00 11	Select WBXML code page 17 (AirSyncBase)
4A	<airsyncbase:Body>, with content
46	<airsyncbase:Type>, with content
03	Inline string follows
31 00	"1"
01	</airsyncbase:Type>
4C	<airsyncbase:EstimatedDataSize>, with content
03	Inline string follows
30 00	"0"

Bytes	Description
01	</airsyncbase:EstimatedDataSize>
4D	<airsyncbase:Truncated>, with content
03	Inline string follows
31 00	"1"
01	</airsyncbase:Truncated>
01	</airsyncbase:Body>
00 01	Select WBXML code page 1 (Contacts)
5E	<contacts:FileAs>, with content
03	Inline string follows
46 75 6E 6B 2C 20 44 6F 6E 00	"Funk, Don"
01	</contacts:FileAs>
5F	<contacts:FirstName>, with content
03	Inline string follows
44 6F 6E 00	"Don"
01	</contacts:FirstName>
69	<contacts:LastName>, with content
03	Inline string follows
46 75 6E 6B 00	"Funk"
01	</contacts:LastName>
00 11	Select WBXML code page 17 (AirSyncBase)
56	<airsyncbase:NativeBodyType>, with content
03	Inline string follows
31 00	"1"
01	</airsyncbase:NativeBodyType>
01	</airsync:ApplicationData>
01	</airsync:Add>
01	</airsync:Commands>
01	</airsync:Collection>
01	</airsync:Collections>
01	</airsync:Sync>

## 4 Security

### 4.1 Security Considerations for Implementers

In most cases, all communication between the client and server happens across an **HTTP** connection secured by the **Secure Sockets Layer (SSL)** protocol. The SSL connection is assumed to be secure enough to transmit confidential data, such as user credentials and sensitive e-mail. The SSL certificate on the server is assumed to be trusted by the client application.

### 4.2 Index of Security Parameters

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

- Microsoft Exchange Server 2007 Service Pack 1 (SP1)
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Windows 8.1
- Windows Communication Apps
- Windows 10 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">2.1.2.1</a> Code Pages	Updated code page tables in sections 2.1.2.1.1 through 2.1.2.1.25 for Exchange ActiveSync protocol version 16.0.	Y	Content update.
<a href="#">5</a> Appendix A: Product Behavior	Updated list of supported products.	Y	Content updated due to protocol revision.



## 7 Index

### A

[Abstract data model](#) 8  
ActiveSync WBXML  
    [overview](#) 8  
[Applicability](#) 7

### C

[Change tracking](#) 39  
[Code pages](#) 8

### D

[Data model - abstract](#) 8

### E

Examples  
    [overview](#) 34

### G

[Glossary](#) 4

### I

[Implementer - security considerations](#) 37  
[Index of security parameters](#) 37  
[Informative references](#) 5  
[Initialization](#) 8  
[Introduction](#) 4

### N

[Normative references](#) 5

### O

[Overview \(synopsis\)](#) 5

### P

[Parameters - security index](#) 37  
[Processing rules](#) 33  
[Product behavior](#) 38

### R

References  
    [informative](#) 5  
    [normative](#) 5  
Relationship to  
    [other algorithms](#) 6  
    [other protocols](#) 6

### S

Security  
    [implementer considerations](#) 37

[parameter index](#) 37  
    [Standards assignments](#) 7

### T

[Tracking changes](#) 39

### W

WBXML  
    [code pages](#) 8