

# [MS-OXSHRMSG]: Sharing Message Attachment Schema

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
11/04/2009	1.0.0	Major	Initial Availability
02/10/2010	1.1.0	Minor	Updated the technical content.
05/05/2010	1.1.1	Editorial	Revised and edited the technical content.
08/04/2010	1.2	Minor	Clarified the meaning of the technical content.
11/03/2010	1.3	Minor	Clarified the meaning of the technical content.

# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Glossary	4
1.2	References	4
1.2.1	Normative References	4
1.2.2	Informative References	5
1.3	Overview	5
1.4	Relationship to Protocols and Other Structures	5
1.5	Applicability Statement	5
1.6	Versioning and Localization	5
1.7	Vendor-Extensible Fields	5
<b>2</b>	<b>Structures</b>	<b>6</b>
2.1	Sharing Message Attachment Namespace	6
2.2	Sharing Message Attachment Processing Instructions	6
2.3	Sharing Message Schema	6
2.3.1	DataTypeType Simple Type	6
2.3.2	InitiatorType Complex Type	7
2.3.3	InvitationType Complex Type	7
2.3.4	t:ProviderType Complex Type	8
2.3.5	t:Providers Complex Type	9
2.3.6	SharingMesasge Element	9
<b>3</b>	<b>Structure Examples</b>	<b>11</b>
<b>4</b>	<b>Security Considerations</b>	<b>13</b>
<b>5</b>	<b>Appendix A: Product Behavior</b>	<b>14</b>
<b>6</b>	<b>Change Tracking</b>	<b>15</b>
<b>7</b>	<b>Index</b>	<b>17</b>

# 1 Introduction

This document specifies the Sharing Message Attachment schema, which defines the schema for an **XML** document that is used to establish a sharing relationship between two servers on behalf of client applications. This document contains identification information and encrypted tokens that enable the two servers to authenticate and establish the sharing relationship.

## 1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

**Augmented Backus-Naur Form (ABNF)**  
**Hypertext Transfer Protocol (HTTP)**  
**shared folder**  
**Uniform Resource Identifier (URI)**  
**XML**  
**XML namespace**  
**XML schema**

The following terms are specific to this document:

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol Specification](#)", November 2009.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC2445] Dawson, F., and Stenerson, D., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", RFC 2445, November 1998, <http://www.ietf.org/rfc/rfc2445.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.ietf.org/rfc/rfc5234.txt>

[XML] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", W3C Recommendation, 16 August 2006, edited in place 29 September 2006, <http://www.w3.org/TR/2006/REC-xml-20060816/>

[XMLENC] Eastlake, D., Ed., Reagle, J., Ed., Imamura, T., et al., "XML Encryption Syntax and Processing", W3C Recommendation, December 2002, <http://www.w3.org/TR/2002/REC-xmlenc-core-20021210/>

[XMLNS] Bray, T., Hollander, D., Layman, A., Eds., et al., "Namespaces in XML 1.0 (Third Edition)", December 2009, <http://www.w3.org/TR/REC-xml-names/>

[XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

## 1.2.2 Informative References

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

## 1.3 Overview

The Sharing Message Attachment schema specifies the authentication and identification information that is required for two servers to set up a sharing relationship on behalf of client applications. The sharing message attachment is composed of three main elements: the type of invitation, the e-mail address and name of the initiator, and the sharing invitation.

## 1.4 Relationship to Protocols and Other Structures

The Sharing Message Attachment schema is used by the Folder Sharing Web Service protocol [\[MS-OXWSMSHR\]](#) to provide authentication and identification information when a **shared folder** relationship is established between two servers. The operations that provide the encrypted token and folder information that is required by the servers to establish the sharing relationship are defined in [\[MS-OXWSMSHR\]](#).

Encrypted data elements of the sharing message structure are defined in [\[MS-OXWSMSHR\]](#). The format of the encrypted data that are contained in the encrypted data elements is defined in [\[XMLENC\]](#).

## 1.5 Applicability Statement

The XML document that is defined by the Sharing Message Attachment schema enables servers to share information on behalf of client applications with less risk of exposing secrets to those client applications. The encrypted data section of the sharing message is passed between the client applications while the information within the sharing message is protected.

## 1.6 Versioning and Localization

This document covers versioning issues in the following areas:

- **Structure versions:** None.
- **Localization:** None.

## 1.7 Vendor-Extensible Fields

None.

## 2 Structures

### 2.1 Sharing Message Attachment Namespace

The elements of the sharing message attachment are defined in the following namespace. See [\[XMLNS\]](#) for the namespaces specification.

<http://schemas.microsoft.com/exchange/sharing/2008/>

Sharing message attachments use encryption elements that are defined by [\[XMLENC\]](#):

<http://www.w3.org/2001/04/xmlenc>

Sharing message attachments use encryption data elements that are defined by [\[MS-OXWSMSHR\]](#):

<http://schemas.microsoft.com/exchange/services/2006/types>

### 2.2 Sharing Message Attachment Processing Instructions

The following XML processing instruction tag, as specified in [\[XML\]](#) section 2.6, MUST appear in the sharing message attachment file:

```
<?xml version="1.0"?>
```

A formal definition in **Augmented Backus-Naur Form (ABNF)**, as specified in [\[RFC5234\]](#), of the XML processing instructions is as follows:

```
UDC_PI = '<?MicrosoftWindowsSharePointServices ' CONTENT_ID_TYPE '?' CRLF
```

```
CONTENT_ID_TYPE = 'ContentTypeID="0x010100B4CBD48E029A4AD8B62CB0E41868F2B0"'
```

### 2.3 Sharing Message Schema

The following sections specify the elements and attributes of the sharing message attachment. The elements and attributes use type definitions from [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

#### 2.3.1 DataTypeType Simple Type

The **DataTypeType** simple type defines the valid sharing message attachment types.

```
<xs:simpleType name="t:DataTypeType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="calendar"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following value is defined by the **t:DataTypeType** simple type:

Value	Description
calendar	The sharing message attachment is for a calendar.

### 2.3.2 InitiatorType Complex Type

The **InitiatorType** complex type specifies the name and e-mail address of the entity that initiates the sharing relationship.

```
<xs:complexType name="InitiatorType">
  <xs:sequence>
    <xs:element name="Name"
      type="xs:string"
    />
    <xs:element name="SmtpAddress"
      type="xs:string"
    />
  </xs:sequence>
</xs:complexType>
```

#### Child Elements

Element	Type	Description
Name	xs:string	The display name of the entity that initiates the sharing relationship.
SmtpAddress	xs:string	The e-mail address of the entity that initiates the sharing relationship.

### 2.3.3 InvitationType Complex Type

The **InvitationType** complex type contains a list of folders to share and the encrypted information that is required to set up the shared folders.

```
<xs:complexType name="InvitationType">
  <xs:sequence>
    <xs:element name="Providers"
      type="t:ProvidersType"
    />
  </xs:sequence>
</xs:complexType>
```

#### Child Elements

Element	Type	Description
Providers	<a href="#">t:ProvidersType</a>	One or more folders to share and the encrypted information that is required to set up the shared folders.

## 2.3.4 t:ProviderType Complex Type

The **ProviderType** complex type specifies a shared folder name and the encrypted information required to set up the shared folder.

```
<xs:complexType name="ProviderType">
  <xs:sequence>
    <xs:element name="FolderId"
      type="xs:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="EncryptedSharedFolderDataCollection"
      type="t:ArrayOfEncryptedSharedFolderDataType"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="BrowseUrl"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="ICalUrl"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
  </xs:sequence>
  <xs:attribute name="Type"
    type="xs:string"
  />
  <xs:attribute name="TargetRecipients"
    type="xs:string"
  />
</xs:complexType>
```

### Child Elements

Element	Type	Description
FolderId	xs:string	The identifier for the shared folder.
EncryptedSharedFolderDataCollection	<a href="#">t:ArrayOfEncryptedSharedFolderDataType</a>	The encrypted authentication token, as specified in <a href="#">[XMLENC]</a> .
BrowseUrl	xs:string	Specifies the <b>URI</b> of a calendar's Web page. MUST be a fully-qualified <b>HTTP</b> URI.
ICalUrl	xs:string	Specifies the URI of the ICalendar format calendar, as



Element	Type	Description
		specified in <a href="#">[RFC2445]</a> . MUST be a fully-qualified HTTP URI.

#### Attributes

Name	Type	Description
Type	xs:string	Specifies the sharing provider type. MUST be either "ms-exchange-external" or "ms-exchange-publish" <a href="#">&lt;1&gt;</a> . If the <b>Type</b> attribute is set to "ms-exchange-publish", the <FolderID> and <EncryptedSharedFolderDefinition> elements MUST be set, and the <BrowseUrl> and <ICalUrl> elements MUST NOT be set. If the <b>Type</b> attribute is set to "ms-exchange-external", the <BrowseUrl> and <ICalUrl> element MUST be set, and the <FolderId> and <EncryptedSharedFolderDefinition> elements MUST NOT be set.
TargetRecipients	xs:string	Specifies a semi-colon delimited list of e-mail addresses that this provider applies to.

### 2.3.5 t:Providers Complex Type

The **ProvidersType** complex type specifies one or more shared folders and the encrypted data that is required to share the folders.

```
<xs:complexType>
  <xs:sequence>
    <xs:element name="Provider"
      type="t:ProviderType"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>
```

#### Child Elements

Element	Type	Description
Provider	<a href="#">t:ProviderType</a>	One or more shared folder providers.

### 2.3.6 SharingMesage Element

The <SharingMessage> element provides a container for the sharing message attachment elements.

```
<xs:element name="SharingMesage">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DataType"
        type="t:DataTypeType"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

    />
    <xs:element name="Initiator"
      type="t:InitiatorType"
    />
    <xs:element name="Invitation"
      type="t:InvitationType"
    />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

### Child Elements

Element	Type	Description
Data Type	<a href="#">t:DataTypeType</a>	The type of the sharing message attachment.
Initiator	<a href="#">t:InitiatorType</a>	The name and e-mail address of the sender of the sharing message attachment.
Invitation	<a href="#">t:InvitationType</a>	The details of the sharing invitation.

### 3 Structure Examples

The following is the complete **XML schema** for the sharing message attachment XML document.

[XML Schema]

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/sharing/2008"
xmlns:tns="http://schemas.microsoft.com/exchange/sharing/2008"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:xml="http://www.w3.org/XML/1998/namespace"
xmlns:enc="http://www.w3.org/2001/04/xmlenc#"
xmlns:ews="http://schemas.microsoft.com/exchange/services/2006/types"
targetNamespace="http://schemas.microsoft.com/exchange/sharing/2008"
elementFormDefault="qualified" version="Exchange2010" id="types">

  <xs:import namespace="http://www.w3.org/2001/04/xmlenc#" />
  <xs:import namespace="http://schemas.microsoft.com/services/exchange/2006/types" />

  <xs:simpleType name="DataTypeType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="calendar" />
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="InitiatorType">
    <xs:sequence>
      <xs:element name="Name" type="xs:string" />
      <xs:element name="SmtpAddress" type="xs:string" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="ProviderType">
    <xs:sequence>
      <xs:element name="FolderId" type="xs:string" />
      <xs:element name="EncryptedSharedFolderDataCollection"
type="ews:ArrayOfEncryptedSharedFolderDataType" />
    </xs:sequence>
    <xs:attribute name="Type" type="xs:string" />
    <xs:attribute name="TargetRecipients" type="xs:string" />
  </xs:complexType>

  <xs:complexType name="ProvidersType">
    <xs:sequence>
      <xs:element name="Provider" type="t:ProviderType" maxOccurs="unbounded" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="InvitationType">
    <xs:sequence>
      <xs:element name="Title" type="xs:string" minOccurs="0" />
      <xs:element name="Providers" type="t:ProvidersType" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="RequestType">
```

```

    <xs:sequence>
      <xs:element name="Providers" type="t:ProvidersType" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="AcceptOfRequestType">
    <xs:sequence>
      <xs:element name="Title" type="xs:string" minOccurs="0" />
      <xs:element name="Providers" type="t:ProvidersType" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="DenyOfRequestType">
    <xs:sequence>
      <xs:element name="Providers" type="t:ProvidersType" />
    </xs:sequence>
  </xs:complexType>

  <xs:element name="SharingMessage">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="DataType" type="t:DataTypeType"/>
        <xs:element name="Initiator" type="t:InitiatorType"/>
        <xs:choice>
          <xs:element name="AcceptOfRequest" type="t:AcceptOfRequestType" />
          <xs:element name="DenyOfRequest" type="t:DenyOfRequestType" />
          <xs:sequence>
            <xs:element name="RequestType" type="t:RequestType" minOccurs="0" />
            <xs:element name="Invitation" type="t:InvitationType" minOccurs="0" />
          </xs:sequence>
        </xs:choice>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:schema>

```

## 4 Security Considerations

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products:

- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 2010 Service Pack 1 (SP1)

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

[<1> Section 2.3.4:](#) Exchange 2010 only accepts the "ms-exchange-external" value for the Type attribute.

## 6 Change Tracking

This section identifies changes that were made to the [MS-OXSHRMSG] protocol document between the August 2010 and November 2010 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- Changes made for template compliance.
- Removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change Type</b>
<a href="#">2.1 Sharing Message Attachment Namespace</a>	58877 Added a reference to the [XMLNS] specification.	N	Content updated.
<a href="#">2.3 Sharing Message Schema</a>	58877 Added references to [XMLSCHEMA1] and [XMLSCHEMA2].	N	Content updated.



## 7 Index

### A

[Applicability](#) 5

### C

[Change tracking](#) 15

### E

[Example](#) 11

### G

[Glossary](#) 4

### I

[Introduction](#) 4

### L

[Localization](#) 5

### N

[Normative references](#) 4

### O

[Overview \(synopsis\)](#) 5

### P

[Product behavior](#) 14

### R

References

[normative](#) 4

[Relationship to protocols and other structures](#) 5

### T

[Tracking changes](#) 15

### V

[Versioning and Localization](#) 5