

[MS-MEDIA-SOURCE]:

Microsoft Edge / Internet Explorer Media Source Extensions Standards Support Document

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
4/25/2017	1.0	New	Released new document.
10/3/2017	1.0	None	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1	Introduction	4
1.1	Glossary	4
1.2	References	4
1.2.1	Normative References	4
1.2.2	Informative References	4
1.3	Microsoft Implementations	4
1.4	Standards Support Requirements	5
1.5	Notation	5
2	Standards Support Statements	6
2.1	Normative Variations	6
2.1.1	[W3C-MEDIA-SOURCE] Section 2. MediaSource Object	6
2.1.2	[W3C-MEDIA-SOURCE] Section 2.1 Attributes	8
2.1.3	[W3C-MEDIA-SOURCE] Section 2.2 Methods	9
2.1.4	[W3C-MEDIA-SOURCE] Section 2.3 Event Summary	9
2.1.5	[W3C-MEDIA-SOURCE] Section 3. SourceBuffer Object	10
2.1.6	[W3C-MEDIA-SOURCE] Section 3.4 Event Summary	12
2.1.7	[W3C-MEDIA-SOURCE] Section 4. SourceBufferList Object	12
2.1.8	[W3C-MEDIA-SOURCE] Section 5. URL Object Extensions	13
2.1.9	[W3C-MEDIA-SOURCE] Section 5.1 Methods	13
2.1.10	[W3C-MEDIA-SOURCE] Section 7. AudioTrack Extensions	14
2.1.11	[W3C-MEDIA-SOURCE] Section 8. VideoTrack Extensions	14
2.1.12	[W3C-MEDIA-SOURCE] Section 9. TextTrack Extensions	15
2.2	Clarifications	15
2.3	Extensions	15
2.4	Error Handling	15
2.5	Security	16
3	Change Tracking	17
4	Index	18

1 Introduction

This document describes the level of support provided by Microsoft web browsers for the W3C *Media Source Extensions* specification [\[W3C-MEDIA-SOURCE\]](#), published 17 November 2016.

The [\[W3C-MEDIA-SOURCE\]](#) specification extends HTMLMediaElement ([\[W3C-HTML51\]](#)) to allow JavaScript to generate media streams for playback. Allowing JavaScript to generate streams facilitates a variety of use cases like adaptive streaming and time shifting live streams.

1.1 Glossary

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[W3C-HTML51] World Wide Web Consortium, "HTML 5.1", W3C Recommendation 1 November 2016, <https://go.microsoft.com/fwlink/p/?linkid=835117>

[W3C-MEDIA-SOURCE] World Wide Web Consortium, "Media Source Extensions™", W3C Recommendation 17 November 2016, <https://go.microsoft.com/fwlink/p/?linkid=835918>

1.2.2 Informative References

None.

1.3 Microsoft Implementations

The following Microsoft web browsers implement some portion of the [\[W3C-MEDIA-SOURCE\]](#) specification:

- Microsoft Edge

Each browser version may implement multiple document rendering modes. The modes vary from one to another in support of the standard. The following table lists the document modes supported by each browser version.

Browser Version	Document Modes Supported
Microsoft Edge	EdgeHTML Mode

For each variation presented in this document there is a list of the document modes and browser versions that exhibit the behavior described by the variation. All combinations of modes and versions that are not listed conform to the specification. For example, the following list for a variation indicates that the variation exists in three document modes in all browser versions that support these modes:
Quirks Mode, IE7 Mode, and IE8 Mode (All Versions)

1.4 Standards Support Requirements

To conform to [\[W3C-MEDIA-SOURCE\]](#) a user agent must implement all required portions of the specification. Any optional portions that have been implemented must also be implemented as described by the specification. Normative language is usually used to define both required and optional portions. (For more information, see [\[RFC2119\]](#).)

The following table lists the sections of [\[W3C-MEDIA-SOURCE\]](#) and whether they are considered normative or informative.

Sections	Normative/Informative
1	Informative
2 - 10	Normative
11 - 13	Informative
Appendices A, B	Informative

1.5 Notation

The following notations are used in this document to differentiate between notes of clarification, variation from the specification, and points of extensibility.

Notation	Explanation
C####	This identifies a clarification of ambiguity in the target specification. This includes imprecise statements, omitted information, discrepancies, and errata. This does not include data formatting clarifications.
V####	This identifies an intended point of variability in the target specification such as the use of MAY, SHOULD, or RECOMMENDED. (See [RFC2119] .) This does not include extensibility points.
E####	Because the use of extensibility points (such as optional implementation-specific data) can impair interoperability, this profile identifies such points in the target specification.

For document mode and browser version notation, see also section [1.3](#).

2 Standards Support Statements

This section contains all variations, clarifications, and extensions for the Microsoft implementation of [\[W3C-MEDIA-SOURCE\]](#).

- Section [2.1](#) describes normative variations from the MUST requirements of the specification.
- Section [2.2](#) describes clarifications of the MAY and SHOULD requirements.
- Section [2.3](#) describes extensions to the requirements.
- Section [2.4](#) considers error handling aspects of the implementation.
- Section [2.5](#) considers security aspects of the implementation.

2.1 Normative Variations

The following subsections describe normative variations from the MUST requirements of [\[W3C-MEDIA-SOURCE\]](#).

2.1.1 [W3C-MEDIA-SOURCE] Section 2. MediaSource Object

V0001: The duration attribute is not unrestricted

The specification states:

```
2. MediaSource Object
```

```
The MediaSource object represents a source of media data for an HTMLMediaElement. It keeps track of the readyState for this source as well as a list of SourceBuffer objects that can be used to add media data to the presentation. ...
```

```
...
```

```
[Constructor]
interface MediaSource : EventTarget {
    ...
    attribute unrestricted double duration;
    ...
};
```

```
2.1 Attributes
```

```
...
duration of type unrestricted double
    Allows the web application to set the presentation duration. The duration is initially set to NaN when the MediaSource object is created.
```

EdgeHTML Mode

The duration attribute is not unrestricted.

```
attribute double duration;
```

V0002: The setLiveSeekableRange and clearLiveSeekableRange methods are not supported

The specification states:

```
2. MediaSource Object
```

The MediaSource object represents a source of media data for an HTMLMediaElement. It keeps track of the readyState for this source as well as a list of SourceBuffer objects that can be used to add media data to the presentation. ...

```
...
[Constructor]
interface MediaSource : EventTarget {
    ...
    void setLiveSeekableRange(double start, double end);
    void clearLiveSeekableRange();
    ...
};

2.2 Methods
...
setLiveSeekableRange
    Updates the live seekable range variable used in HTMLMediaElement Extensions to
    modify HTMLMediaElement.seekable behavior.
...
clearLiveSeekableRange
    Updates the live seekable range variable used in HTMLMediaElement Extensions to
    modify HTMLMediaElement.seekable behavior.
```

EdgeHTML Mode

The setLiveSeekableRange and clearLiveSeekableRange methods are not supported.

V0003: The sourceopen, sourceended, and sourceclose events are not supported

The specification states:

2. MediaSource Object

The MediaSource object represents a source of media data for an HTMLMediaElement. It keeps track of the readyState for this source as well as a list of SourceBuffer objects that can be used to add media data to the presentation. ...

```
...
[Constructor]
interface MediaSource : EventTarget {
    ...
    attribute EventHandler sourceopen;
    attribute EventHandler sourceended;
    attribute EventHandler sourceclose;
    ...
};

2.1 Attributes
...
onsourceopen of type EventHandler
    The event handler for the sourceopen event.
onsourceended of type EventHandler
    The event handler for the sourceended event.
onsourceclose of type EventHandler
    The event handler for the sourceclose event.
```

2.3 Event Summary

Event Name	...
-----	...
sourceopen	...
sourceended	...
sourceclose	...

EdgeHTML Mode

The `onsourceopen`, `onsourceended`, and `onsourceclose` events are not supported.

2.1.2 [W3C-MEDIA-SOURCE] Section 2.1 Attributes

V0001: The duration attribute is not unrestricted

The specification states:

2. MediaSource Object

The `MediaSource` object represents a source of media data for an `HTMLMediaElement`. It keeps track of the `readyState` for this source as well as a list of `SourceBuffer` objects that can be used to add media data to the presentation. ...

```
...  
  [Constructor]  
  interface MediaSource : EventTarget {  
    ...  
    attribute unrestricted double duration;  
    ...  
  };
```

2.1 Attributes

```
...  
duration of type unrestricted double  
  Allows the web application to set the presentation duration. The duration is  
  initially set to NaN when the MediaSource object is created.
```

EdgeHTML Mode

The `duration` attribute is not unrestricted.

```
  attribute double duration;
```

V0003: The `sourceopen`, `sourceended`, and `sourceclose` events are not supported

The specification states:

2. MediaSource Object

The `MediaSource` object represents a source of media data for an `HTMLMediaElement`. It keeps track of the `readyState` for this source as well as a list of `SourceBuffer` objects that can be used to add media data to the presentation. ...

```
...  
  [Constructor]  
  interface MediaSource : EventTarget {  
    ...  
    attribute EventHandler sourceopen;  
    attribute EventHandler sourceended;  
    attribute EventHandler sourceclose;  
    ...  
  };
```

2.1 Attributes

```
...  
sourceopen of type EventHandler  
  The event handler for the sourceopen event.  
sourceended of type EventHandler  
  The event handler for the sourceended event.  
sourceclose of type EventHandler
```


The event handler for the sourceclose event.

2.3 Event Summary

```
Event Name    ...
-----      ...
sourceopen    ...
sourceended   ...
sourceclose   ...
```

EdgeHTML Mode

The onsourceopen, onsourceended, and onsourceclose events are not supported.

2.1.3 [W3C-MEDIA-SOURCE] Section 2.2 Methods

V0002: The setLiveSeekableRange and clearLiveSeekableRange methods are not supported

The specification states:

2. MediaSource Object

The MediaSource object represents a source of media data for an HTMLMediaElement. It keeps track of the readyState for this source as well as a list of SourceBuffer objects that can be used to add media data to the presentation. ...

```
...
[Constructor]
interface MediaSource : EventTarget {
    ...
    void setLiveSeekableRange(double start, double end);
    void clearLiveSeekableRange();
    ...
};
```

2.2 Methods

```
...
setLiveSeekableRange
    Updates the live seekable range variable used in HTMLMediaElement Extensions to
    modify HTMLMediaElement.seekable behavior.
...
clearLiveSeekableRange
    Updates the live seekable range variable used in HTMLMediaElement Extensions to
    modify HTMLMediaElement.seekable behavior.
```

EdgeHTML Mode

The setLiveSeekableRange and clearLiveSeekableRange methods are not supported.

2.1.4 [W3C-MEDIA-SOURCE] Section 2.3 Event Summary

V0003: The sourceopen, sourceended, and sourceclose events are not supported

The specification states:

2. MediaSource Object

The MediaSource object represents a source of media data for an HTMLMediaElement. It

keeps track of the readyState for this source as well as a list of SourceBuffer objects that can be used to add media data to the presentation. ...

```
...
[Constructor]
interface MediaSource : EventTarget {
    ...
    attribute EventHandler sourceopen;
    attribute EventHandler sourceended;
    attribute EventHandler sourceclose;
    ...
};
```

2.1 Attributes

```
...
onsourceopen of type EventHandler
    The event handler for the sourceopen event.
onsourceended of type EventHandler
    The event handler for the sourceended event.
onsourceclose of type EventHandler
    The event handler for the sourceclose event.
```

2.3 Event Summary

Event Name	...
-----	...
sourceopen	...
sourceended	...
sourceclose	...

EdgeHTML Mode

The onsourceopen, onsourceended, and onsourceclose events are not supported.

2.1.5 [W3C-MEDIA-SOURCE] Section 3. SourceBuffer Object

V0004: The textTracks attribute is not supported

The specification states:

```
3. SourceBuffer Object
...
interface SourceBuffer : EventTarget {
    ...
    readonly attribute TextTrackList textTracks;
    ...
};
```

EdgeHTML Mode

The textTracks attribute is not supported.

V0005: The appendWindowEnd attribute is not unrestricted

The specification states:

```
3. SourceBuffer Object
...
interface SourceBuffer : EventTarget {
```

```
...
attribute unrestricted double appendWindowEnd;
...
};
```

EdgeHTML Mode

The `appendWindowEnd` attribute is not unrestricted.

```
attribute double appendWindowEnd;
```

V0006: Events are not supported on the `SourceBuffer` interface

The specification states:

```
3. SourceBuffer Object
...
interface SourceBuffer : EventTarget {
...
attribute EventHandler onupdatestart;
attribute EventHandler onupdate;
attribute EventHandler onupdateend;
attribute EventHandler onerror;
attribute EventHandler onabort;
...
};
```

3.4 Event Summary

```
Event name ...
----- ...
updatestart ...
update ...
updateend ...
error ...
abort ...
```

EdgeHTML Mode

Events are not supported on the `SourceBuffer` interface.

V0007: The end argument of the `remove` function is not unrestricted

The specification states:

```
3. SourceBuffer Object
...
interface SourceBuffer : EventTarget {
...
void remove(double start, unrestricted double end);
};
```

EdgeHTML Mode

The end argument of the `remove` function is not unrestricted.

```
void remove(double start, double end);
```

2.1.6 [W3C-MEDIA-SOURCE] Section 3.4 Event Summary

V0006: Events are not supported on the SourceBuffer interface

The specification states:

```
3. SourceBuffer Object
...
interface SourceBuffer : EventTarget {
    ...
    attribute EventHandler onupdatestart;
    attribute EventHandler onupdate;
    attribute EventHandler onupdateend;
    attribute EventHandler onerror;
    attribute EventHandler onabort;
    ...
};
```

3.4 Event Summary

```
Event name ...
----- ...
updatestart ...
update ...
updateend ...
error ...
abort ...
```

EdgeHTML Mode

Events are not supported on the SourceBuffer interface.

2.1.7 [W3C-MEDIA-SOURCE] Section 4. SourceBufferList Object

V0008: The events on the SourceBufferList interface are not supported

The specification states:

4. SourceBufferList Object

SourceBufferList is a simple container object for SourceBuffer objects. It provides read-only array access and fires events when the list is modified.

```
interface SourceBufferList : EventTarget {
    ...
    attribute EventHandler onaddsourcebuffer;
    attribute EventHandler onremovesourcebuffer;
    ...
};
```

EdgeHTML Mode

The events on the SourceBufferList interface are not supported.

2.1.8 [W3C-MEDIA-SOURCE] Section 5. URL Object Extensions

V0009: The createObejctURL method is defined incorrectly

The specification states:

5. URL Object Extensions

This section specifies extensions to the URL[FILE-API] object definition.

```
[Exposed=Window]
partial interface URL {
    static DOMString createObjectURL(MediaSource mediaSource);
};
```

5.1 Methods

```
createObjectURL, static
    Creates URLs for MediaSource objects.
```

EdgeHTML Mode

The createObejctURL method is defined incorrectly and is not defined as an override method to the similarly named methods defined in other specifications.

```
interface URL {
    static DOMString createObjectURL(any object, optional ObjectURLOptions options = 0);
};
```

2.1.9 [W3C-MEDIA-SOURCE] Section 5.1 Methods

V0009: The createObejctURL method is defined incorrectly

The specification states:

5. URL Object Extensions

This section specifies extensions to the URL[FILE-API] object definition.

```
[Exposed=Window]
partial interface URL {
    static DOMString createObjectURL(MediaSource mediaSource);
};
```

5.1 Methods

```
createObjectURL, static
    Creates URLs for MediaSource objects.
```

EdgeHTML Mode

The createObejctURL method is defined incorrectly and is not defined as an override method to the similarly named methods defined in other specifications.

```
interface URL {
    static DOMString createObjectURL(any object, optional ObjectURLOptions options = 0);
```

```
};
```

2.1.10 [W3C-MEDIA-SOURCE] Section 7. AudioTrack Extensions

V0010: The sourceBuffer attribute is not defined as nullable

The specification states:

7. AudioTrack Extensions

This section specifies extensions to the HTML AudioTrack definition.

```
partial interface AudioTrack {  
    readonly attribute SourceBuffer? sourceBuffer;  
};
```

8. VideoTrack Extensions

This section specifies extensions to the HTML VideoTrack definition.

```
partial interface VideoTrack {  
    readonly attribute SourceBuffer? sourceBuffer;  
};
```

EdgeHTML Mode

The sourceBuffer attribute is not defined as nullable.

```
partial interface AudioTrack {  
    readonly attribute SourceBuffer sourceBuffer;  
};  
  
partial interface VideoTrack {  
    readonly attribute SourceBuffer sourceBuffer;  
};
```

2.1.11 [W3C-MEDIA-SOURCE] Section 8. VideoTrack Extensions

V0010: The sourceBuffer attribute is not defined as nullable

The specification states:

7. AudioTrack Extensions

This section specifies extensions to the HTML AudioTrack definition.

```
partial interface AudioTrack {  
    readonly attribute SourceBuffer? sourceBuffer;  
};
```

8. VideoTrack Extensions

This section specifies extensions to the HTML VideoTrack definition.

```
partial interface VideoTrack {
    readonly attribute SourceBuffer? sourceBuffer;
};
```

EdgeHTML Mode

The `sourceBuffer` attribute is not defined as nullable.

```
partial interface AudioTrack {
    readonly attribute SourceBuffer sourceBuffer;
};

partial interface VideoTrack {
    readonly attribute SourceBuffer sourceBuffer;
};
```

2.1.12 [W3C-MEDIA-SOURCE] Section 9. TextTrack Extensions

V0011: The `sourceBuffer` attribute is not supported

The specification states:

9. TextTrack Extensions

This section specifies extensions to the HTML TextTrack definition.

```
partial interface TextTrack {
    readonly attribute SourceBuffer? sourceBuffer;
};
```

EdgeHTML Mode

The `sourceBuffer` attribute is not supported.

2.2 Clarifications

There are no clarifications of the MAY and SHOULD requirements of [\[W3C-MEDIA-SOURCE\]](#).

2.3 Extensions

There are no extensions to the requirements of [\[W3C-MEDIA-SOURCE\]](#).

2.4 Error Handling

There are no additional error handling considerations.

2.5 Security

There are no additional security considerations.

3 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

4 Index

C

[Change tracking](#) 17

G

[Glossary](#) 4

I

[Informative references](#) 4

[Introduction](#) 4

N

[Normative references](#) 4

R

References

[informative](#) 4

[normative](#) 4

T

[Tracking changes](#) 17